



OPEN ENDED TIMING BELTS

Description

MEDWAY Open Ended Timing Belts are manufactured in both rubber and thermoplastic polyurethane giving superior wear and abrasion resistance, specifically suitable for linear drives, accurate positioning and reversal drives. A high load capacity, low maintenance costs and very low noise levels, make open ended belts a perfect alternative to chain or cable linear drives.

Features include; Consistent dimensional stability, low pre-tension, low noise, high abrasion resistance, low maintenance, high flexibility, linear speeds up to 80 m/sec, high precision linear positioning.

Open ended rubber and polyurethane timing belts are produced in both straight and spiral cut options and are available in the following cross sections; 3M, 5M, 8M, XL, L, H, T5 & T10.

OPEN ENDED TIMING BELTS - RUBBER

Part Number	Width	Width	Width	Width	Width	Width	Width	Width	Width
3M-	15mm	-	-	-	-	-	-	-	-
5M-	15mm	25mm	-	-	-	-	-	-	-
8M-	15mm	20mm	30mm	50mm	85mm	-	-	-	-
XL-	1/4" (025)	5/16" (031)	3/8" (037)	-	-	-	-	-	-
L-	-	-	3/8" (037)	1/2" (050)	3/4" (037)	1" (100)	-	-	-
H-	-	-	-	1/2" (050)	3/4" (037)	1" (100)	1-1/2" (150)	2" (200)	3" (300)

OPEN ENDED TIMING BELTS - POLYURETHANE

Part Number	Width	Width	Width	Width	Width	Width	Width
5M-	15mm	25mm	-	-	-	-	-
8M-	-	20mm	30mm	50mm	85mm	-	-
T5-	8mm	10mm	12mm	16mm	25mm	-	-
T10-	-	-	12mm	16mm	25mm	32mm	50mm